

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First Named Inventor:	Ulrich Haueter	
Appln. No.:	Unknown	
Filed:	Herewith	Examiner: Unknown
Title:	Measuring Device for Body Fluids and Infusion Set and Dialysis Probe Comprising Such a Measuring Device	Group Art Unit: Unknown

PRELIMINARY AMENDMENT


Box PATENT APPLICATION

Express Mail Mailing Label No: EV040317537US

Commissioner for Patents Washington, D.C. 20231

Date of Deposit: March 1, 2008

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner for Patents, Washington, D.C. 20231

Signature: 

Dear Sir:

Prior to examination of the above-identified patent application, please amend it as follows:

IN THE SPECIFICATION

After the title, please insert the following:

--Priority Claim

This application is a continuation of International Patent Application PCT/CH00/00456, filed on August 29, 2000, which claims priority to an earlier filed German Application Number DE 199 42 898 A1, filed on September 8, 1999.--

IN THE ABSTRACT

Please replace the originally filed abstract with the following:

--The invention relates to a measuring device for body fluids, comprising an access to the interior of the body and a sensor to which the body fluid to be measured is supplied via the access. The sensor is arranged on a part of the measuring device outside the body, in the

100875375 030108

immediate vicinity of the end, outside the body, of the access . The invention further relates to an infusion set and a dialysis probe comprising such a measuring device.--

IN THE CLAIMS

Please cancel original claims 1-7 and substitute new claim 8-20 as follows:

8. (New) A measuring device for measuring body fluids, comprising an access structure for accessing the interior of the body, said access structure having an end coupled to the measuring device, and a sensor to which the body fluid to be measured is supplied via said access structure, said sensor arranged on said measuring device outside the body, in the immediate vicinity of the end of said access structure.
9. (New) The measuring device as set forth in claim 8, wherein said sensor is arranged such that it may be removed and replaced.
10. (New) The measuring device as set forth in claim 8, wherein said access structure provides a fluid channel for providing a fluid flow, said device further comprising a valve means arranged in the fluid channel for preventing a reverse flow of fluid from said sensor into said access structure.
11. (New) The measuring device as set forth in claim 8, further comprising an infusion set comprising a catheter head, wherein said sensor is arranged on the catheter head.
12. (New) The measuring device as set forth in claim 8, further comprising an implanted dialysis probe having an outlet outside the body, wherein said sensor is arranged in the outlet.
13. (New) An infusion set comprising a measuring device as set forth in claim 8.

14. (New) A dialysis probe comprising a measuring device as set forth in claim 8.
15. (New) A dialysis probe comprising a probe head and access structure coupled to the probe head and comprising a supply tube and a discharge tube, at least a portion of the discharge tube lying outside a patient's body when in use and carrying a sensor.
16. (New) The dialysis probe according to claim 15, said probe head further comprising an inlet and an outlet, said inlet coupled to the supply tube, said outlet coupled to the discharge tube.
17. (New) The dialysis probe according to claim 16, the sensor adjacent to the coupling of the discharge tube and the outlet.
18. (New) The dialysis probe according to claim 17, wherein the sensor is immediately adjacent to the patient's body when the probe is in use.
19. (New) The dialysis probe according to claim 18, further comprising a reflux valve associated with the outlet.
20. (New) The dialysis probe according to claim 18, further comprising a valve associated with the outlet for selectively controlling the flow of dialysis fluid.

REMARKS

The above amendments are being made to clarify the priority claim and to conform the claims to U.S. practice.

The added claims do not generate any additional claims fees in excess of the basic filing fee. The Commissioner is hereby authorized to charge Deposit Account No. 04-1420 in the amount of \$740.00 to cover the basic filing fee is enclosed, and the Office is also hereby authorized to charge any deficiency, or credit any overpayment associated with this communication to Deposit Account 04-1420.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned "**Marked-up Version Showing Changes.**"

Early allowance is respectfully requested.

Respectfully submitted,

DORSEY & WHITNEY LLP

Date:

Mar 1, 2002

By:

David E. Bruhn

David E. Bruhn (Reg. No. 36,762)
Suite 1500
50 South Sixth Street
Minneapolis, MN 55402-1498
(612) 340-6317

MARKED-UP VERSION SHOWING CHANGES**IN THE SPECIFICATION****Priority Claim**

This application is a continuation of International Patent Application PCT/CH00/00456, filed on August 29, 2000, which claims priority to an earlier filed German Application Number DE 199 42 898 A1, filed on September 8, 1999.

IN THE ABSTRACT

The invention relates to a measuring device for body fluids, comprising an access [(2)] to the interior of the body and a sensor [(1)] to which the body fluid to be measured is supplied via the access [(2)]. The sensor [(1)] is arranged on a part of the measuring device outside the body, in the immediate vicinity of the end, outside the body, of the access [(2)]. The invention further relates to an infusion set and a dialysis probe comprising such a measuring device.

IN THE CLAIMS

Please cancel original claims 1-7, and add new claims 8-20 as follows:

8. (New) A measuring device for measuring body fluids, comprising an access structure for accessing the interior of the body, said access structure having an end coupled to the measuring device, and a sensor to which the body fluid to be measured is supplied via said access structure, said sensor arranged on said measuring device outside the body, in the immediate vicinity of the end of said access structure.

9. (New) The measuring device as set forth in claim 8, wherein said sensor is arranged such that it may be removed and replaced.

-
10. (New) The measuring device as set forth in claim 8, wherein said access structure provides a fluid channel for providing a fluid flow, said device further comprising a valve means arranged in the fluid channel for preventing a reverse flow of fluid from said sensor into said access structure.
11. (New) The measuring device as set forth in claim 8, further comprising an infusion set comprising a catheter head, wherein said sensor is arranged on the catheter head.
12. (New) The measuring device as set forth in claim 8, further comprising an implanted dialysis probe having an outlet outside the body, wherein said sensor is arranged in the outlet.
13. (New) An infusion set comprising a measuring device as set forth in claim 8.
14. (New) A dialysis probe comprising a measuring device as set forth in claim 8.
15. (New) A dialysis probe comprising a probe head and access structure coupled to the probe head and comprising a supply tube and a discharge tube, at least a portion of the discharge tube lying outside a patient's body when in use and carrying a sensor.
16. (New) The dialysis probe according to claim 15, said probe head further comprising an inlet and an outlet, said inlet coupled to the supply tube, said outlet coupled to the discharge tube.
17. (New) The dialysis probe according to claim 16, the sensor adjacent to the coupling of the discharge tube and the outlet.
18. (New) The dialysis probe according to claim 17, wherein the sensor is immediately adjacent to the patient's body when the probe is in use.
19. (New) The dialysis probe according to claim 18, further comprising a reflux valve associated

with the outlet.

20. (New) The dialysis probe according to claim 18, further comprising a valve associated with the outlet for selectively controlling the flow of dialysis fluid.